

IPT PRESET CLICK WRENCH

- Durable and robust for industrial fastening applications.
- Preset wrench ensures that the correct torque value is consistently applied to each bolt.
- Tamper-proof internal adjustment. No external adjustment scale - must be preset using a torque analyzer. Requires Torque Adjusting Key (sold separately).
- Built with a robust steel shaft with high corrosion resistance.
- Lightly knurled non-slip grip.
- Bi-directional ratchet head (48 tooth ratchet).
- Positive click can be heard and felt when torque is reached.
- The preferred and certified ranges of these tools are in accordance with the requirements of ISO 6789 (+/- 4% of indicated setting).



Torque Ranges

Models	Item #	American	S.I.	Drive Size	Length	Weight lbs.
IPT 18	280041	3.7 - 18.4 lbf.ft	5 - 25 N.m	1/4" Sq. Dr.	8 7/8"	0.7
IPT 36	280042	7.4 - 36.9 lbf.ft	10 - 50 N.m	3/8" Sq. Dr.	11 7/8"	1.4
IPT 73	280043	14.8 - 73.8 lbf.ft	20 - 100 N.m	3/8" Sq. Dr.	14 3/4"	1.8
IPT 110	280044	22.1 - 110.7 lbf.ft	30 - 150 N.m	3/8" Sq. Dr.	15 1/4"	2.4
IPT 150	280045	29.5 - 147.6 lbf.ft	40 - 200 N.m	1/2" Sq. Dr.	19 2/3"	2.9
IPT 250	280046	44.3 - 250.9 lbf.ft	60 - 340 N.m	1/2" Sq. Dr.	23 1/8"	3.9
IPT 369	280047	73.8 - 369 lbf.ft	100 - 500 N.m	3/4" Sq. Dr.	34"	12.1
IPT 885	280048	171.1 - 885.6 lbf.ft	240 - 1200 N.m	1" Sq. Dr.	58 1/4"	13

Related Products



IPT Torque Adjusting Set Key

The IPT Torque Adjusting Set Key is required to adjust the internal torque setting for select models

Item # 280049

For: IPT 18 - IPT 250 models.

Note! A 3mm allen key, extension bar, and a ratchet wrench or handle are needed to adjust the internal torque setting for models: IPT 369 - IPT 885 models