









Mountz Torque FG Preset Torque Screwdrivers



Total Torque Control At Your Fingertips

Preset torque screwdrivers improve productivity by consistently applying the correct torque value to each fastener. Preset torque screwdrivers are ideal for fastening applications where operators repeatedly assemble parts at the same torque setting. A preset screwdriver doesn't have an external torque adjustment scale.

These tools have an internal torque adjustment mechanism for setting the torque value and preset using a hex key and a torque analyzer. The locking mechanism prevents accidental torque setting changes. Designed for industries where production errors aren't acceptable, poka-yoke torque screwdriver prevents over-torque events.

				
Product Name	FG Mini Preset Screwdriver	FG Preset Screwdriver	FG IFR Preset	FG OWC Preset Screwdriver
Torque Range	3 - 25 ozf.in 10 - 50 ozf.in	0.8 - 8 lbf.in 2 - 20 lbf.in 4 - 40 lbf.in 25 - 125 lbf.in	0.8 - 8 lbf.in 2 - 20 lbf.in 4 - 40 lbf.in 25 - 125 lbf.in	0.8 - 8 lbf.in 2 - 20 lbf.in 4 - 40 lbf.in 25 - 125 lbf.in
Tool Length	4.1 in	5.2 - 6.3 in*	5.2 - 6.3 in*	5.2 - 6.3 in*
Cam-Over Mechanism	X	X	X	X
Ensure correct torque is applied to reduce fastener breakage				
Tamper-Proof Internal Adjustment Seal	X	X	X	X
No external adjustment. Seal to prevent adjustment tampering				
Color-Coded Label Options				
Mark tools for easy-to-understand torque setting identification				
Ergonomic Handles	X	X	X	X
Designed with fewer flutes and larger recesses to reduce hand fatigue				
Low-Impact Reset Mechanism			X	
Ideal for assembling shock-sensitive components				
One-Way Clutch Technology				X
Designed for easy screw removal. Ideal for maintenance and refurbishing applications				
Calibration Life	5,000 cycles (ISO Standard)	20,000 cycles (4x ISO Standard)	20,000 cycles (4x ISO Standard)	20,000 cycles (4x ISO Standard)
4x ISO Standard Calibration Life		X	X	X
Reduce tool downtime. Unmatched by any torque screwdriver				
2-Year Unconditional Warranty	X	X	X	X
lifetime against defects				

* 5.2 in tool length applies to 0.8 - 8 lbf.in and 2 - 20 lbf.in torque range

* 6.3 in tool length applies to 4 - 40 lbf.in and 25 - 125 lbf.in torque range

Distributor:



Intercal (Pty) Ltd.
Email: sales@intercal.co.za
Phone: +27 11 315 4321

